



Light

EVELYN 01

Lightweight and breathable all day long

Evelyn is designed to ensure long-lasting comfort with modern style and easy fitting. All extra safety features are making this work shoe ideal for professionals in demanding environments, who spend many hours standing and that have the need for lightweight footwear. A perfect fit for everyone with an active life.

Upper	Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Safety standard	O1 / ESD, SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.195 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018




LBL



BLK




WHT



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Medical, Catering, Cleaning, Food & beverages

Environments:

Extreme slippery surfaces, Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Mesh			
	Upper: permeability to water vapor	mg/cm ² /h	50.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	404	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	43.7	≥ 2
	Lining: water vapor coefficient	mg/cm ²	350	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Phylon/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	129	≤ 150
	Outsole slip resistance SRA: heel	friction	0.37	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.21	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	80.6	0.1 - 100
Heel energy absorption	J	28	≥ 20	

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.