

HENNY **OB**

Sporty and fashionable sneaker for him

Upper	Synthetic Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	TPR
Safety standard	OB / E, SRA
Size range	EU 39-47 / UK 6.0-12.0 US 6.5-13.0 / CM 25.5-31.0
Sample weight	0.390 kg
Norms	EN ISO 20347:2012









Coolmax[®] lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



Industries:

Cleaning, Food & beverages, Medical

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347		
Upper	Synthetic Leather					
	Upper: permeability to water vapor	mg/cm²/h	1.1	≥ 0.8		
	Upper: water vapor coefficient	mg/cm²	16.8	≥ 15		
Lining	Mesh					
	Lining: permeability to water vapor	mg/cm²/h	51	≥ 2		
	Lining: water vapor coefficient	mg/cm²	408.7	≥ 20		
Footbed	SJ foam footbed					
	Footbed: abrasion resistance	cycles	400	≥ 400		
Outsole	TPR					
	Outsole abrasion resistance (volume loss)	mm³	145	≤ 150		
	Outsole slip resistance SRA: heel	friction	0.31	≥ 0.28		
	Outsole slip resistance SRA: flat	friction	0.48	≥ 0.32		
	Outsole slip resistance SRB: heel	friction	NA	≥ 0.13		
	Outsole slip resistance SRB: flat	friction	NA	≥ 0.18		
	Antistatic value	MegaOhm	NA	0.1 - 1000		
	ESD value	MegaOhm	NA	0.1 - 100		
	Heel energy absorption	J	24	≥ 20		

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and maynot be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

