

# KAYLA 02

### Soft full-leather work sneaker for comfort, safety and style!

Kayla is a sporty comfort work sneaker with smooth breathable leather that covers your foot like a glove. This work sneaker protects against trips, slips, and falls thanks to the SRC slipresistance outsole. On top of all this, the brand-new SJ Foam footbed brings perfect cushioning making this sneaker perfect for work and home.

| Upper           | Nappa Leather                                       |
|-----------------|---|
| Lining          | Mesh  |
| Footbed         | SJ foam footbed                                     |
| Outsole         | Phylon/Rubber                                       |
| Safety standard | O2 / ESD, SRC                                       |
| Size range      | EU 35-42 / UK 3.0-8.0<br>US 5.5-10.5 / CM 23.0-27.0 |
| Sample weight   | 0.280 kg  |
| Norms           | EN ISO 20347:2012<br>ASTM F2892:2018                |



BLK









Breathable leather upper

Natural leather provides a

combined with durability in

versatile applications.

high degree of wearer comfort















## Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



#### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



#### **SRC** slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### **Electrostatic Discharge (ESD)**

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.





#### **Industries:**

Catering, Cleaning, Food & beverages, Medical, Uniform

## **Environments:**

Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

## **Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|         | Description                               | Measure unit | Result | EN ISO 20347 |  |  |
|---------|---|--------------|--------|--------------|--|--|
| Upper   | Nappa Leather                             |              |        |              |  |  |
|         | Upper: permeability to water vapor        | mg/cm²/h     | 2.73   | ≥ 0.8        |  |  |
|         | Upper: water vapor coefficient            | mg/cm²       | 28     | ≥ 15         |  |  |
| Lining  | Mesh                                      |              |        |              |  |  |
|         | Lining: permeability to water vapor       | mg/cm²/h     | 21.1   | ≥ 2          |  |  |
|         | Lining: water vapor coefficient           | mg/cm²       | 169    | ≥ 20         |  |  |
| Footbed | SJ foam footbed                           |              |        |              |  |  |
|         | Footbed: abrasion resistance              | cycles       | 400    | ≥ 400        |  |  |
| Outsole | Phylon/Rubber                             |              |        |              |  |  |
|         | Outsole abrasion resistance (volume loss) | mm³          | 47     | ≤ 150        |  |  |
|         | Outsole slip resistance SRA: heel         | friction     | 0.42   | ≥ 0.28       |  |  |
|         | Outsole slip resistance SRA: flat         | friction     | 0.38   | ≥ 0.32       |  |  |
|         | Outsole slip resistance SRB: heel         | friction     | 0.14   | ≥ 0.13       |  |  |
|         | Outsole slip resistance SRB: flat         | friction     | 0.18   | ≥ 0.18       |  |  |
|         | Antistatic value                          | MegaOhm      | NA     | 0.1 - 1000   |  |  |
|         | ESD value                                 | MegaOhm      | 57.3   | 0.1 - 100    |  |  |
|         | Heel energy absorption                    | J            | 22     | ≥ 20         |  |  |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and maynot be used or reproduced in any format, without written consent from us.



