



LUCA 01

Light, breathable sneaker for him

Upper	Textile
Lining	Elastic Mesh
Footbed	Mesh
Outsole	Rubber
Safety standard	O1 / ESD, SRC
Size range	EU 39-47 / UK 6.0-12.0 US 6.5-13.0 / CM 25.5-31.0
Sample weight	0.254 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



LGR



NAV




Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Memory foam

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Catering, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Textile			
	Upper: permeability to water vapor	mg/cm²/h	22.8	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	183.6	≥ 15
Lining	Elastic Mesh			
	Lining: permeability to water vapor	mg/cm²/h	40.2	≥ 2
	Lining: water vapor coefficient	mg/cm²	321.7	≥ 20
Footbed	Mesh			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Rubber			
	Outsole abrasion resistance (volume loss)	mm³	123	≤ 150
	Outsole slip resistance SRA: heel	friction	0.45	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.47	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.23	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.21	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	1.4	0.1 - 100
	Heel energy absorption	J	30	≥ 20

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com