



LUCIA 01

Closed shoe with an elegant touch

Outsole	Rubber
Safety standard	O1 / ESD, SRC
Size range	EU 35-10H / UK 3.0 US 5.5 / CM 23.0
Sample weight	0.234 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



FLR



BLK



FUX



LBL




LGN



PTB



WHT



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Outsole	Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	117	≤ 150
	Outsole slip resistance SRA: heel	friction	0.49	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.46	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	14.3	0.1 - 1000
	ESD value	MegaOhm	34.0	0.1 - 100
	Heel energy absorption	J	42.0	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.