



Medium

ROMAN 01

Airy and trendy sneaker for him

| | |
|-----------------|--|
| Upper | Synthetic Leather |
| Lining | Mesh |
| Footbed | Oxy Hybrid |
| Outsole | Phylon/Rubber |
| Safety standard | O1 / ESD, SRC |
| Size range | EU 39-47 / UK 6.0-12.0 US 6.5-13.0 / CM 25.5-31.0 |
| Sample weight | 0.275 kg |
| Norms | EN ISO 20347:2012 ASTM F2892:2018 |



BLK



GRY




Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Memory foam

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|--------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 3.5 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 30 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 24.1 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 193 | ≥ 20 |
| Footbed | Oxy Hybrid | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | Phylon/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 121 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.45 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.47 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.19 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.21 | ≥ 0.18 |
| | Antistatic value | MegaOhm | NA | 0.1 - 1000 |
| | ESD value | MegaOhm | 25 | 0.1 - 100 |
| | Heel energy absorption | J | 27 | ≥ 20 |

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.